



A RUTHMAN COMPANY

GUSHER®

Industrial and Coolant Pumps

www.Gusher.com

7800 Series Vertical Discharge Pumps

Models:

11019 A

NEW!...V11019 SE

11031 NS

11032 NS

11034 NS

Features, Dimensions
and Performance Data






RUTHMAN
Engineering Pump Solutions®



11019 AVD-SE

2HP



ALSO AVAILABLE
IN HORIZONTAL

Model: 11019 AVD-SE

Speed: 3450 RPM

Hertz: 60




Impeller Dia: 4.250

Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor	Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min	NPT 1.5	inch mm	HP kw	3 phase	current Amps	current Amps
Z217888 (STD)	12.812	325.4	140	63.64	50	189.25		13.75	2			
Z217889 (+6")	18.812	477.8	162	73.64	Ft.	m		349.25	1.49	208/230	5.2	6.5
Z217890 (+12")	24.812	630.2	184	83.64	80	24.39				460	2.6	3.25
Z217891 (+18")	30.812	782.6	206	93.64								
Z217892 (+24")	36.812	935	228	103.64								



11019 AVD-SE

3HP



ALSO AVAILABLE
IN HORIZONTAL



Model: 11019 AVD-SE Speed: 3450 RPM Hertz: 60 Impeller Dia: 4.625

Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor		Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch	mm	HP	kw	3 phase	current Amps
Z217897 (STD)	12.812	325.4	140	63.64	100	378.5	NPT 1.5	13.75	349.3	3	2.24	208/230	7.43
Z217898 (+6")	18.812	477.8	162	73.64	Ft.	m						460	9.29
Z217899 (+12")	24.812	630.2	184	83.64	85	25.91							3.715
Z217900 (+18")	30.812	782.6	206	93.64									4.645
Z217901 (+24")	36.812	935.0	228	103.64									



11019 AVD-SE

5HP



ALSO AVAILABLE
IN HORIZONTAL



Model: 11019 AVD-SE Speed: 3450 RPM Hertz: 60 Impeller Dia: 5.750

Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor	Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min	NPT 1.5	inch mm	HP kw	3 phase	current Amps	current Amps
Z217902 (STD)	12.812	325.4	210	95.45	100	378.5		15	5			
Z217903 (+6")	18.812	477.8	232	105.45	Ft.	m		381	3.73	208/230	11.8	14.8
Z217904 (+12")	24.812	630.2	254	115.45	138	42.07				460	5.9	7.4
Z217905 (+18")	30.812	782.6	276	125.45								
Z217906 (+24")	36.812	935.0	298	135.45								




11019 AVD-SE

7.5HP



1/4" NPT FOR PRESSURE GAGE



ALSO AVAILABLE IN HORIZONTAL

Model: 11019 AVD-SE Speed: 3450 RPM Hertz: 60 Impeller Dia: 6.350


Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height	Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		Motor inch mm				
Z217907 (STD)	12.812	325.4	226	102.73	135	510.975	NPT 1.5	16.5	7.5	208/230 460	17.3 8.65	21.6 10.8
Z217908 (+6")	18.812	477.8	248	112.73	Ft.	m		419.1	5.60			
Z217909 (+12")	24.812	630.2	270	122.73	150	45.73						
Z217910 (+18")	30.812	782.6	292	132.73								
Z217911 (+24")	36.812	935.0	314	142.73								



11019 AVD Performance Data


VERT7800 - 3000 Catalog: Gusher Pump Catalog 50Hz, Vers 3.0

Size: 11019SE-A Speed: 2875 rpm Dia: 6.35 in





VERT7800 - 3600 Catalog: Gusher Pump Catalog 60Hz, Vers 3.0

Size: 11019SE-A Speed: 3450 rpm Dia: 6.35 in





2HP



ALSO AVAILABLE
IN HORIZONTAL



7

NEW!...FROM GUSHER...V11019-SE SERIES




V11019 AVD-SE

3HP



1/4" NPT FOR
PRESSURE GAGE





ALSO AVAILABLE
IN HORIZONTAL

NEW!...FROM GUSHER...V11019-SE SERIES




V11019 AVD-SE

5HP



1/4" NPT FOR PRESSURE GAGE



ALSO AVAILABLE
IN HORIZONTAL




CONTACT GUSHER FOR MORE INFORMATION...859-824-3100

NEW!...FROM GUSHER...V11019-SE SERIES




V11019 AVD-SE

7.5HP



ALSO AVAILABLE
IN HORIZONTAL

Performance
Data
for
Vortex
V11019
AVD-SE








11031NS-SE-VD

7.5HP

(ALSO 5HP)



Model: 11031NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 6




Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor		Power		Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch	mm	HP	kw	3 phase	current Amps	current Amps
Z217912 (STD)	13.75	349.3	260	118.18	150	567.75	NPT 2	16.562	420.67	7.5	5.60	208/230	17.3	21.6
Z217913 (+6")	19.75	501.7	282	128.18	Ft.	m						460	8.65	10.8
Z217914 (+12")	25.75	654.1	304	138.18	130	39.63								
Z217915 (+18")	31.75	806.5	326	148.18										
Z217916 (+24")	37.75	958.9	348	158.18										



11031NS-SE-VD

10HP

WITH IMPELLER DIAMETER 6.375



Model: 11031NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 6.375




Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor	Power		Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch mm	HP	kw	3 phase	current Amps	current Amps
Z217917 (STD)	13.75	349.3	260	118.18	150	567.75	NPT 2	16.562	10				
Z217918 (+6")	19.75	501.7	282	128.18				420.67	7.46		208/230	23.4	29.3
Z217919 (+12")	25.75	654.1	304	138.18	170	51.83					460	11.7	14.65
Z217920 (+18")	31.75	806.5	326	148.18									
Z217921 (+24")	37.75	958.9	348	158.18									



11031NS-SE-VD

10HP

WITH IMPELLER DIAMETER 6.125






Model: 11031NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 6.125

Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height	Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		Motor inch mm				
Z217922 (STD)	13.75	349.3	320	145.45	200	757	NPT 2	16.562	10 7.46	3 phase 208/230 460	current Amps 23.4 11.7	current Amps 29.3 14.65
Z217923 (+6")	19.75	501.7	342	155.45	Ft.	m		420.67				
Z217924 (+12")	25.75	654.1	364	165.45	130	39.63						
Z217925 (+18")	31.75	806.5	386	175.45								
Z217926 (+24")	37.75	958.9	408	185.45								



11031NS-SE-VD

15HP



Model: 11031NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 6.615


Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height		Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch	mm			current Amps	current Amps
Z218142 (STD)	13.75	349.3	345	156.82	200	757	NPT 3	16.562 420.6748	15 11.19	3 phase 208/230 460		33.6 16.8	42 21
Z218143 (+6")	19.75	501.7	367	166.82	Ft.	m							
Z218144 (+12)	25.75	654.1	389	176.82	170	51.83							
Z218145 (+18)	31.75	806.5	411	186.82									
Z218146 (+24)	37.75	958.9	433	196.82									



11031NS Performance Data


VERT7800 - 3000 Catalog: Gusher Pump Catalog 50Hz, Vers 3.0

Size: 11031E-CIHorJP Speed: 2860 rpm Dia: 6.615 in



VERT7800 - 3600 Catalog: Gusher Pump Catalog 60Hz, Vers 3.0

Size: 11031E-CIHorJP Speed: 3480 rpm Dia: 6.615 in








11032NS-SE-VD

10HP

(ALSO 7.5HP)






Model: 11032NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 5.375

Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height		Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch	mm			current	
Z217938 (STD)	13.937	354.0	335	152.27	250	946.25	NPT 3	16.562	420.67	10	208/230 460	23.4	29.3
Z217939 (+6")	19.937	506.4	357	162.27						7.46		11.7	14.65
Z217940 (+12")	25.937	658.8	379	172.27	110	33.54							
Z217941 (+18")	31.937	811.2	401	182.27									
Z217942 (+24")	37.937	963.6	423	192.27									



11032NS-SE-VD

15HP






Model: 11032NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 6.00

Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor		Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch	mm			current Amps	current Amps
Z217943 (STD)	13.937	354.0	360	163.64	300	1135.5	NPT 3	16.562 420.67	15 11.19	3 phase 208/230 460		33.6 16.8	42 21
Z217944 (+6")	19.937	506.4	382	173.64	Ft.	m							
Z217945 (+12")	25.937	658.8	404	183.64	140	42.68							
Z217946 (+18")	31.937	811.2	426	193.64									
Z217947 (+24")	37.937	963.6	448	203.64									



11032NS-SE-VD

20HP






Model: 11032NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 6.50

Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor		Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch	mm	HP	kw	3 phase	current Amps
Z218096 (STD)	13.937	354.0	450	204.55	350	1324.8	NPT 3	13.75	349.3	20	14.93	208/230	46.6
Z218097 (+6)	19.937	506.4	472	214.55	Ft.	m						460	58.26
Z218098 (+12)	25.937	658.8	494	224.55	160	48.78							23.3
Z218099 (+18)	31.937	811.2	516	234.55									29.13
Z218100 (+24)	37.937	963.6	538	244.55									



11032NS-SE-VD

25HP



Model: 11032NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 6.625


Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor	Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min	NPT 3	inch mm	HP kw	3 phase	current Amps	current Amps
Z218101(STD)	13.937	354.0	590	268.18	400	1514		26.062	25 18.66	208/230	58	72.6
Z218102 (+6)	19.937	506.4	612	278.18	Ft.	m		661.97				
Z218103 (+12)	25.937	658.8	634	288.18	160	48.78						
Z218104 (+18)	31.937	811.2	656	298.18								
Z218105 (+24)	37.937	963.6	678	308.18								



11032NS Performance Data


VERT7800 - 3000 Catalog: Gusher Pump Catalog 50Hz, Vers 3.0

Size: 11032E-CIHOrJP Speed: 2860 rpm Dia: 6.625 in



VERT7800 - 3600 Catalog: Gusher Pump Catalog 60Hz, Vers 3.0

Size: 11032E-CIHOrJP Speed: 3450 rpm Dia: 6.625 in








11034NS-SE-VD

7.5HP

WITH IMPELLER DIAMETER 7.250



ALSO AVAILABLE IN HORIZONTAL

Model: 11034NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 7.250




Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor	Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch mm	HP kw	3 phase	current Amps	current Amps
Z218112 (STD)	13	330.2	270	122.73	50	189.25	NPT 1.5	16.5	7.5	208/230 460	17.3	21.6
Z218113 (+6)	19	482.6	292	132.73	Ft.	m		419.1	5.60			
Z218114 (+12)	25	635.0	314	142.73	231	70.43						
Z218115 (+18)	31	787.4	336	152.73								
Z218116 (+24)	37	939.8	358	162.73								



11034NS-SE-VD

7.5HP

WITH IMPELLER DIAMETER 6.750



ALSO AVAILABLE
IN HORIZONTAL




Model: 11034 NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 6.750

Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor	Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch mm	HP kw	3 phase	current Amps	current Amps
Z218117 (STD)	13	330.2	270	122.73	100	378.5	NPT 1.5	16.5	7.5	208/230 460	17.3	21.6
Z218118 (+6)	19	482.6	292	132.73	Ft.	m		419.1	5.60			
Z218119 (+12)	25	635.0	314	142.73	190	57.93						
Z218120 (+18)	31	787.4	336	152.73								
Z218121 (+24)	37	939.8	358	162.73								



11034NS-SE-VD

10HP



ALSO AVAILABLE
IN HORIZONTAL



Model: 11034NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 6.875

Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor	Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min	NPT 1.5	inch mm	HP kw	3 phase	current Amps	current Amps
Z218122 (STD)	13	330.2	325	147.73	150	567.75		16.562	10			
Z218123 (+6)	19	482.6	347	157.73	Ft.	m		420.67	7.46	208/230	23.4	29.3
Z218124 (+12)	25	635.0	369	167.73	180	54.88				460	11.7	14.65
Z218125 (+18)	31	787.4	391	177.73								
Z218126 (+24)	37	939.8	413	187.73								




11034NS-SE-VD

15HP



1/4" NPT FOR PRESSURE GAGE



ALSO AVAILABLE
IN HORIZONTAL



Model: 11034NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 7.355

Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor		Power		Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch	mm	HP	kw	3 phase	current Amps	current Amps
Z218127 (STD)	13	330.2	280	127.27	200	757	NPT 1.5	16.562	420.67	15	11.19	208/230	33.6	42
Z218128 (+6")	19	482.6	302	137.27	Ft.	m		420.67		11.19		460	16.8	21
Z218129 (+12)	25	635.0	324	147.27	180	54.88								
Z218130 (+18)	31	787.4	346	157.27										
Z218131 (+24)	37	939.8	368	167.27										



11034NS-SE-VD

20HP



ALSO AVAILABLE
IN HORIZONTAL




Model: 11034NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 8.000

Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height Motor		Power		Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch	mm	HP	kw	3 phase	current Amps	current Amps
Z218132 (STD)	13	330.2	440	200.00	200	757	NPT 1.5	22.25	565.15	20	14.93	208/230 460	58	72.6
Z218133 (+6)	19	482.6	462	210.00	Ft.	m								
Z218134 (+12)	25	635.0	484	220.00	248	75.61								
Z218135 (+18)	31	787.4	506	230.00										
Z218136 (+24)	37	939.8	528	240.00										



11034NS-SE-VD

25HP



ALSO AVAILABLE
IN HORIZONTAL

Model: 11034NS-SE-VD Speed: 3450 RPM Hertz: 60 Impeller Dia: 8.062


Z number	Depth of immersion		Weight		Flow @ Head		Thread	Height		Power	Voltage	Rated	SF
	inch	mm	lbs	kg	Gpm	l/min		inch	mm			current Amps	
Z218186	13	330.2	585	265.91	260	984.1	NPT 3	26.062	661.9748	25 18.66	3 phase	58	72.6
Z218187	19	482.6	607	275.91	Ft.	m					208/230	29	36.3
Z218188	25	635.0	629	285.91	190	57.93					460		
Z218189	31	787.4	651	295.91									
Z218190	37	939.8	673	305.91									



11034NS Performance Data


VERT7800 - 3000 Catalog: Gusher Pump Catalog 50Hz, Vers 3.0

Size: 11034-E Speed: 2860 rpm Dia: 8.0625 in



VERT7800 - 3600 Catalog: Gusher Pump Catalog 60Hz, Vers 3.0

Size: 11034-E Speed: 3500 rpm Dia: 8.0625 in





A RUTHMAN COMPANY

www.Gusher.com

GUSHER PUMPS LOCATIONS

Williamstown Headquarters

115 Industrial Road
Williamstown, KY 41097
Phone: 859.824.5001
Fax: 859.824.3011
Email: Info@Gusher.com

Dry Ridge Manufacturing

22 Ruthman Drive
Dry Ridge, KY 41035
Phone: 859.824.5001
Fax: 859.824.3011
Email: Info@Gusher.com

Dry Ridge Training Facility

3565 Dixie Highway
Dry Ridge, KY 41035
Phone: 859.824.5001
Email: Info@Gusher.com

New Castle Sales & Service

403 North Ninth Street
New Castle, IN 47362
Phone: 765.529.5624
Fax: 765.521.0008
Email: GusherNC@Gusher.com

Gusher Pumps, Shanghai

655 Caosheng Rd, Jiading District
Shanghai, China 201808
Phone: +86 (021) 55151993
Email: Flomo@Gusher.com

Ruthman Companies: A family-owned business supplying pumps for over 100 years



Ruthman Companies was co-founded in 1912 by brothers Alois and Edward Ruthman as the Ruthman Machinery Company. Based in Cincinnati, the company serviced the steamboats that traveled the Ohio River.

In 1924, Alois conceived the first sealless centrifugal pump, coining the term "coolant pump." The brothers named this new pump "Gusher," giving birth to what is now Ruthman Companies' flagship brand, Gusher Pumps.

Alois's son Thomas R. Ruthman joined the family business in 1949, growing the business globally through organic growth and the acquisition of complementary technologies. In the early 1990s, Alois's grandson, Thomas G. Ruthman, became the third generation of Ruthmans in the pump business. Over the years, Ruthman Companies has expanded its product line from the original centrifugal coolant pumps to include valves, vertical turbine pumps, positive displacement pumps, gear pumps, and other specialized pump equipment, while upholding its reputation as a leader in the custom engineering of pumps for the most challenging applications.

RUTHMAN COMPANIES MANUFACTURING DIVISIONS

BSM Pump Corp.

180 Frenchtown Road
North Kingstown, RI 02852
Phone: 401.471.6350
Fax: 401.471.6370
Email: Sales@BSMPump.com
www.BSMPump.com

Fulflo Hydraulic Valves

459 East Fancy Street
Blanchester, OH 45107
Phone: 937.783.2411
Fax: 937.783.4983
Email: Info@Fulflo.com
www.Fulflo.com

Nagle Pumps

1249 Center Avenue
Chicago Heights, IL 60411
Phone: 708.754.2940
Fax: 708.754.2944
www.NaglePumps.com

Process Systems Inc., Headquarters

23633 Pinewood Street
Warren, MI 48091
Phone: 586.757.5711
Fax: 586.758.6996
Email: Sales@PSI4Pumps.com
www.PSI4Pumps.com

Process Systems Inc., Midwest Service

485 N. State Route 341 South
Mellott, IN 47958
Phone: 765.295.2206
Fax: 765.295.2343
Email: Sales@PSI4Pumps.com
www.PSI4Pumps.com

RAE Pumps

1212 Streng Street
Cincinnati, OH 45223
Phone: 513.779.3034
www.RuthmanCompanies.com

Ruthman Pumps & Service

1212 Streng Street
Cincinnati, OH 45223
Phone: 513.559.3546
www.RuthmanCompanies.com

RUTHMAN COMPANIES GLOBAL DIVISIONS

Ruthmann Pumpen, LLC

Thomas-Edison-Str. 11
D-52499 Baesweiler
Germany
Phone: +49 (0) 2401 80489-0
Fax: + 49 (0) 2401 80489-20
Email: Info@RuthmannPumpen.de
www.RuthmannPumpen.de

RUTHMAN COMPANIES HEADQUARTERS

7236 Tylers Corner Drive
West Chester, OH 45069
Phone: 513.559.1901
www.RuthmanCompanies.com



RUTHMAN
Engineering Pump Solutions™